


1-Line, Bi-directional, Transient Voltage Suppressor




Features

- Stand-off voltage: $\pm 5\text{V}$ Max
- Transient protection for each line according to IEC61000-4-2(ESD): $\pm 30\text{kV}$ (contact)
IEC61000-4-4 (EFT): 40A (5/50ns)
IEC61000-4-5(surge): 8A (8/20 μs)
- Ultra-low capacitance: $C_J = 10\text{pF}$ typ
- Low leakage current
- Low clamping voltage: $V_{CL}=10.0\text{V}$ typ. @ $I_{PP} = 16\text{A}$ (TLP)
- Solid-state silicon technology

Mechanical Data

- **Package:** DFN0603-2L
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** No marking on bi-directional types
- **Marking:** A5

■Definitions of electrical characteristics





ESD5V0LZB

■Maximum Ratings


PARAMETER	SYMBOL	Rating	UNIT
-----------	--------	--------	------

Peak pulse power (t




■ Characteristics (Typical)

8/20 μ s waveform per IEC61000-4-5



Clamping voltage vs. Peak pulse current

Contact discharge current waveform per IEC61000-4-2



Capacitance vs. Reverse voltage

Non-repetitive peak pulse power vs. Pulse time

Power derating vs. Ambient temperature



ESD/Clamping





■ Recommend land pattern (Unit:mm)



Notes:

This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met

