


## N-Channel Enhancement Mode Field Effect Transistor



### Product Summary

$V_{DS}$	100V
$I_D$	58A
$R_{DS(ON)}$ ( at $V_{GS}=10V$ )	12m
$R_{DS(ON)}$ ( at $V_{GS}=4.5V$ )	17m
100% EAS Tested	
100% $V_{DS}$ Tested	

### General Description

**Excellent package for heat dissipation**

**< high density cell design for low  $R_{DS(ON)}$**

**Moisture Sensitivity Level 1**

**Epoxy Meets UL - 0 Flammability Rating**

**Part no. with suffix Q1 means AEC-Q101 qualified**

### Applications

Power switching application

Uninterruptible power supply

DC-DC convertor

12V,24V and 48V Automotive system

### Absolute Maximum Ratings ( $T_A=25$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-source Voltage	$V_{DS}$	100	V
Gate-source Voltage	$V_{GS}$	$\pm 20$	V

Drain Current		58	
	$T_C=100$	41	
Pulsed Drain Current <sup>A</sup>	$I_{DM}$	180	A
Avalanche energy <sup>B</sup>	EAS	81	mJ
Total Power Dissipation <sup>C</sup>	$T_A=25$	2.7	W
	$T_A=100$	1.8	
	$T_C=25$	100	
	$T_C=100$	50	
Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 +175	




Thermal resistance









Typical Electrical and Thermal Characteristics Diagrams





# YJG58G10BQ








# YJG58G10BQ

## PDFN5060-8L-B-1.1MM Package information





# YJG58G10BQ

---

## Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics    ✘