



N-Channel Enhancement Mode Field Effect Transistor

Product Summary

V_{DS}	40V
I_D	225A
$R_{DS(ON)}$ (at $V_{GS}=10V$)	1.2m
100% EAS Tested	
100% V_{DS} Tested	

General Description

Excellent package for heat dissipation
High density cell design for low $R_{DS(ON)}$
Epoxy Meets UL 94 V-0 Flammability Rating
Halogen Free

-Q101 qualified

Applications

High power inverter system
Uninterruptible power supply
LCDM appliances

Absolute Maximum Ratings ($T_A=25$ unless otherwise noted)

Parameter		Symbol	Limit	Unit
Drain-source Voltage		V_{DS}	40	V
Gate-source Voltage		V_{GS}	± 20	V
Drain Current	$T_A=25$	I_D	25	A
	$T_A=100$		17.8	
	$T_C=25$		225	
	$T_C=100$		159	
Pulsed Drain Current ^A		I_{DM}	400	A
Avalanche energy ^B		EAS	1441	mJ
Total Power Dissipation ^C	$T_A=25$	P_D	2	W
	$T_A=100$		1	
	$T_C=25$		166	
	$T_C=100$		8	



YJT225G04HJQ

RECOMMEND
[YJT1D3G04HQ](#)
FOR NEW DESIGN

Electrical Characteristics ($T_J=25$ unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Static Parameter						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V, I_D$	40	-		



Typical Electrical and Thermal Characteristics Diagrams

Figure




Figure 13. Maximum Transient Thermal Impedance



Figure 14. Safe Operation Area

NOT RECOMMEND
FOR NEW DESIGN

**TOLL Package information**

SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	2.2	2.3	2.4
A1	1.7	1.8	1.9
b	0.7	0.8	0.9
b1	9.7	9.8	9.9
b2	1.1	1.2	1.3
c	0.4	0.5	0.6
D	10.28	10.38	10.48
D1	10.98	11.08	11.18
D2	3.2	3.3	3.4
D3	4.45	4.55	4.65
E	9.8	9.9	10
E1	8	8.1	8.2
e	1.2 BSC		
H	11.58	11.68	11.78
H1	6.95 BSC		
i	0.1 REF		
j	0.46 REF		
L	1.5	1.6	1.7
L1	0.6	0.7	0.8
L2	0.5	0.6	0.7
L3	0.3	0.4	0.5
Q	8 REF		
R	3.0	3.1	3.2

Note:

1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.03\text{mm}$.
3. The pad layout is for reference purposes only.

NOT RECOMMENDED
FOR NEW DESIGN



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, life-saving, lifesustaining, or military, Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com>

NOT RECOMMENDED
FOR NEW DESIGN