

Dual PNP Small Signal Transistor



Features

- Epoxy meets UL-94 V-0 flammability rating
- Reduces number of components and board space
- No mutual interference between the transistors
- Part no. with suffix "Q" means AEC-Q101 qualified


Application

- General purpose Switching and Amplification

Mechanical Data

- Package: SOT-363
- Terminals: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- Marking: 5Ft

Equivalent circuit



■Maximum Ratings (Ta=25 Unless otherwise specified)

Item	Symbol	Unit	Value
Collector-Base Voltage	V_{CBO}	V	-80
Collector-Emitter Voltage	V_{CEO}	V	-65
Emitter-Base Voltage	V_{EBO}	V	-5
Collector Current	I_C	mA	-100
Total Device Dissipation (*)	P_C	mW	200
Thermal Resistance Junction to Ambient (*)	R_{thJA}	K/W	625
Junction Temperature	T_j		-55 to +150
			-55 to +150

(*) Device mounted on FR-4 PCB 1.0 x 1.0 x 0.06 inch

BC856BSQ





Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

' produisth ь efb 'Meя m lăу Tdesбя ьтнТi i ьдiдiнT ь IMM .oт]