



# 1H1G THRU 1H8G

## High Efficient Rectifier

### Features

- High efficiency
- High current capability
- High Reliability
- High surge current capability
- Glass passivated chip junction
- Solder dip 275 °C max. 7 s, per JESD 22-B106

### Mechanical Data

Package: R-1

11M688ing.com

A

	FSM	A	30		
Forward Surge Current (Non-repetitive) @ 1ms, square wave, 1 cycle, Tj=25			60		
Current squared time @ 1ms t8.3 ms Tj=25 Rating of per diode	I <sup>2</sup> t	A <sup>2</sup> s	3.735		
Typical junction capacitance @ Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	Cj	pF	15	13	8
Storage Temperature	Tstg		-55 ~ +150		
Junction Temperature	Tj		-55 ~ +150		

### Electrical Characteristics Ta=25 Unless otherwise specified

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	1H1G	1H2G	1H3G	1H4G	1H5G	1H6G	1H7G	1H8G
Maximum instantaneous forward voltage drop per diode	VF	V	IFM=1.0A	1.0			1.3		1.7		
Maximum DC reverse current at rated DC blocking voltage per diode	IR	μA	Tj=25								

+ \* 7 + 5 8 + \*

---

v7KHUPDO &KDUDÄF7HULVWLFV



**Outline Dimensions**



# 1H1G THRU 1H8G

---

## Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherY Re M M hi i