


## Super Fast Recovery Rectifier




### Features

- Ultrafast reverse recovery time
- Low leakage current
- Low switching losses, high efficiency
- High forward surge capability
- Glass passivated chip junction
- Solder dip 275 °C max. 7 s, per JESD 22-B106

### Typical Applications

For use in high frequency rectification and freewheeling application in switching mode converters and inverters for consumer, computer and telecommunication.



### Mechanical Data

**Package:** DO-204AC(DO-15)

Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant

**Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

**Polarity:** Color band denotes the cathode end

### Maximum Ratings (Ta=25 Unless otherwise specified)


PARAMETER	SYMBOL	UNIT	SF29G
Device marking code			SF29G
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	V	800
Maximum RMS Voltage	$V_{RMS}$	V	560
Maximum DC blocking Voltage	$V_{DC}$	V	800
Average Forward Current @60Hz sine wave, Resistance load, Ta =50	$I_{F(AV)}$	A	2.0
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, Tj=25	$I_{FSM}$	A	50
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25			100
Current squared time @1ms t8.3 ms Tj=25 Rating of per diode	$I^2t$	A <sup>2</sup> s	10.375
Typical junction capacitance @Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	$C_j$	pF	13
Storage Temperature	$T_{stg}$		-55 ~ +150
Junction Temperature	$T_j$		-55 ~ +150

### Electrical Characteristics Ta=25 Unless otherwise specified


PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	SF29G
Maximum instantaneous forward voltage drop per diode	$V_F$	V	$I_{FM}=2.0A$	1.7
Maximum DC reverse current at rated DC blocking voltage per diode	$I_R$	$\mu A$	$T_j=25$	2.5
			$T_j=125$	100
Maximum reverse recovery time	$t_{rr}$	ns	$I_F=0.5A, I_R=1.0A, I_r=0.25A$	35



FIG.5: Diagram of circuit and Testing wave form of reverse recovery time



## Outline Dimensions



DO-204AC(DO-15)		
Dim	Min	Max
A	5.80	7.60
B	2.60	3.60
C	25.4	/
D	0.70	0.90



## Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use