



MK5045

Schottky Bypass Diode Module

6AE(© * ñD ¼ ±1Ñ Q ‡

Features/ × ñ(©&é

" +LJK IUHTXHQQFQ ÑŠ HEDWLRQ
" /RZ IRUZDUG YR'QWLDJH GURS
" +LJK SXULW\ KXUK WŠRŠSHUQFV SVXODWLRQ
HQKDQFHG PHFKDQDQDOP RWWUMXUW KUHVLVWDQ
Q4ß Ö ÄQ\$Y)ß"W1>ð ÈjàjÖ ¼Lb%ž W -
"ORQJ WHUPKTUOH QLVDELOLW\

Typical Applications/ " » Ä+X

3KRWRYROWDLFHVRQDQ FHFQVSWRWUHFWLILH
y?ZLc7-+e"• Ö6AE(© * ñ#q~

Mechanical Data/ × ñ ò

Package/ 1>ð: *) 6
"OROGLQJ FRPSRXQG PHHWD/PDELOLW\
UDW+1@É1V8 8/ 9 'óW1y4x
"Terminals/ E7J€É: 7LQ SODWHG OHDGV VROGHUDE
- 67' DQG -(6' K%pKQE4iÈ':W1V
8- 67' -(6' %7ð
"Polarity/ ±W: \$V PDUNLQJ

Maximum Ratings 7D 8QOHVV RWKHUÄLVWNÉHF&ŠYHG D L" MŽ 9Êy

PARAMETER ð	SYMBOL 1V'	UNIT ... }	MK5045
----------------	---------------	---------------	--------

'HYLFH PDUNLQJ FRGH
× ñ »'

0.

&XUUHQW 6TXDUHG 7LPH # PV"W PV 7M
!"A#Š#¼•, +e•#qÉé&•L\$8° €V `€VQ0\$YS p €, ,

Å7

7M

a

127(Ö 0HHWV WKH UHTXLUHPHQWV RI ,(&UPDO(ÖHVHMSDVV GLRGH WKH
Ö Ä Å% Cã, (& (GñD ¼ ±1Ñ' W7-?±"r

Electrical Characteristics Ä7D 8QOHVV RWKHUÄLVWNÉHF&ŠYHG D L" MŽ 9?ð Ê

	1V'	UNIT ... }	TEST CONDITIONS #(B'&	MK5045
0D[LPXP LQVWDQWDQHRXV IRUZDUG YROWDJH 0W!"A-Ü & »L}		GURS 9 SHU	GLR,QH \$!"A0 W+e#q \$	



MK5045

Thermal Characteristics

PARAMETER	SYMBOL	UNIT	MK5045
-----------	--------	------	--------

7KHUPDO 5HÄLVWDQFH

MK5045



MK5045

Disclaimer
>CS

7KH LQIRUPDWLRQ SURFHVW LQ WKLV LQIRUPDWLRQ HQWURQLF (QFORQLF /WG IHUδ