



MBR3045CTS

" Terminals 7LQ SODWHG OHDGV VROGHUDEOH S
DQG -(6' %
" Polarity \$V PDUNHG

Maximum Ratings 8QOHVV RWKHU¹ ALVH VSHFLILHG

PARAMETER	SYMBOL	UNIT	MBR3045CTS
'HYLFH PDUNLQJ FRGH			0%5 &76
5HSHWLWLYH 3HDN 5HYHUVH 9950WDJH		9	
\$YHUDJH 5HFWLILHG 2XWSXW &XUUHQW # +] VLQH ZDYH 5 ORDG 7F ,2		\$	
6XUJH 1RQ UHSHWLWLYH)RUZDUG &XUUHQW # +] KDOI VLQH ZDYH - FROH '60		\$	
&XUUHQW 6TXDUHG 7LPH # PV"W" PV 7	,W	\$V	
6WRUDJH 7HPSHUDWXUH	7VWJ	-	a

			&21',7,216	0%5 &76
0D[LPXP LQVWDQWDQHRXV)RUZDUG YROWDJH GURS SHU GLRGH	0		,0	\$



MBR3045CTS

Thermal Characteristics 7D 8QOHVV RWKHUÄLVH VSHFLILHG

PARAMETER		SYMBOL	UNIT	MBR3045CTS
7KHUPDO 5HVLVWDQFH	%HWZHHQ 5MXQFWLRQ ĐQG			FDVH

Ordering Information ([DP SOH

PREFERRED P/N	UNIT WEIGHT(g)	MINIIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
0 % 5 & 7 6	\$SSUR[LPDWH				

7XEH

Characteristics 7\SLFDO

FIG3: Forward Voltage




FIG.4: Typical Reverse Characteristics

